AMENDMENTS TO THE CLAIMS

The claims in this listing will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

- (Currently Amended) Method for producing a fiber-composite material for producing fiber-composite components, the fiber-composite material comprising combining reinforcement fibers, resin, and a filler, the filler comprising at least one of ground and cut reinforcement fibers so that the filler comprises a same material as the reinforcement fibers.
- (Previously Presented) Method according to claim 1, wherein the filler comprises ground fibers having a particle size of less than 2 mm.
- (Previously Presented) Method according to claim 1, wherein the filler comprises cut fibers having a size of less than 20 mm.
- 4. (Currently Amended) Method according to claim 1, wherein the at least one of ground and cut reinforcement fibers is mixed with the resin that forms a subsequent matrix of the fiber-composite component thereby forming a resin filler mixture.
- (Previously Presented) Method according to claim 4, wherein the resin filler mixture is processed into a film.
- (Previously Presented) Method according to claim 5, wherein the resin filler film is applied to a semi-finished textile product.
- (Previously Presented) Method according to claim 6, wherein the resin filler film is introduced into a component mold before the semi-finished textile product is placed in the component mold.

00671939.DOC

- 8. (Previously Presented) Method according to claim 1, wherein the fiber-composite material is applied into a component mold or onto a semi-finished textile product in a spray method.
- (Previously Presented) Method according to claim 8, wherein the semi-finished textile product sprayed with the resin filler material is also used for producing preforms.
 - 10. (Canceled)
- 11. (Previously Presented) Method according to claim 6, wherein the semi-finished textile product comprises woven fabrics, braided fabrics, knitted fabrics, unidirectional fabrics or multiaxial laid fabrics.
- (Previously Presented) Method according to claim 7, wherein the resin filler film comprises a preform.
- 13. (New) The method according to claim 1, wherein the filler comprises ground fibers having a particle size of less than 2 mm, and cut fibers having a size of less than 20 mm.
 - 14. (New) Fiber-composite material produced by the method of claim 1.
 - 15. (New Fiber-composite material produced by the method of claim 2.
 - 16. (New) Fiber-composite material produced by the method of claim 3.
 - 17. (New) Fiber-composite material produced by the method of claim 13.
- 18. (New) Fiber-composite material comprising reinforcement fibers, resin, and a filler comprising the reinforcement fibers that are at least one of ground and cut so that the filler comprises a same material as the reinforcement fibers.
- 19. (New) Fiber-composite material according to claim 18, wherein the filler comprises at least one of ground fibers having a particle size of less than 2 mm, and cut fibers having a size of less than 20 mm.

00671939.DOC

20. (Previously Presented) The fiber-composite material according to claim 18, wherein the filler comprises ground fibers having a particle size of less than 2 mm, and cut fibers having a size of less than 20 mm.